

LUXORJET

- 1. White colour as a background on the whole surface of the glass trophy
- 2. White colour as a background under the colour pixels
- 3. Slightly transparent colour print (without a white colour)

Tips when preparing the artwork by yourself

LUXORJET

If the coloured background has to reach the edge of the glass, extend beyond the outline of the glass 5 mm on each side.

minimum resolution for illustrations or photos 300 dpi

The artwork should be prepared in CMYK palette

external outline of the glass - TEMPLATE
please do not change the color and thickness of the line

all fonts converted to curves

smallest font used 8 pt

minimum thickness of lines used in the design 0.2 mm

an area where essential elements should be placed, i.e. text, logo, etc.

80024

80023

80022

80021

ETUI

80024
80023
80022
80021

ENGRAVING

Tips when preparing the artwork by yourself

external outline of the glass - TEMPLATE
please do not change the color and thickness of the line

all fonts converted to curves

smallest font used 8 pt

minimum thickness of lines used in the design 0.2 mm

laser engraving area

we only use vector objects (inscriptions, logos, characters)

the pattern for engraving will be prepared in grey using 70 % black in C M Y K scale

when filling with paint, please specify colour (print palette in separate file)

ENGRAVING

! Because of manual processing of the glass trophies, template may slightly differ from the final product.

80024

80023

80022

80021

engraving area

engraving area

engraving area

engraving area