

LUXORJET

1. White colour as a background on the whole surface of the glass trophy
2. White colour as a background under the colour pixels
3. Slightly transparent colour print (without a white colour)

Tips when preparing the artwork by yourself

LUXORJET

if the coloured background has to reach the edge of the glass
extend it beyond the outline of the glass 8 mm on each side

minimum resolution for illustrations
or photos 300 dpi

The artwork should be prepared in CMYK palette

external outline of the class - TEMPLATE

please do not change the color
and thickness of the line

all fonts converted to curves

minimum thickness of lin

In this design 0.2 mm

114

placed, i.e. text, logo, etc.

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

ETUI

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

ENGRAVING

Tips when preparing the artwork by yourself

external outline of the glass - TEMPLATE

and thickness of the line

smallest font used 8 pt

minimum thickness of lines used
in the drawing **0.2 mm**

laser engraving area

```
we only use vector objects
(inscriptions, logos, characters)
```

the pattern for engraving will be prepared in grey using 70 % black in C M Y K scale

when filling with paint, **please specify**
 (paint palette in separate file)

ENGRAVING

! Because of manual processing of the glass trophic, template may slightly differ from the final product.

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

engraving area