

LUXORJET

1. White colour as a background on the whole surface of the glass trophy
2. White colour as a background under the colour pixels
3. Slightly transparent colour print (without a white colour)

Tips when preparing the artwork by yourself

LUXORJET

if the coloured background has to reach the edge of the glass, please extend it beyond the outline of the glass 8 mm on each side.

minimum resolution for illustrations
or photos 300 dpi

**The artwork should be prepared
in CMYK palette**

external outline of the glass - **TEMPLATE**
please do not change the color
and thickness of the line

all fonts converted to curves

smallest font used 8 pt

minimum thickness of lines used
in the design 0.2 mm

an area where essential elements should be placed, i.e. text, logo, etc.

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

ETUI

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

ENGRAVING

Tips when preparing the artwork by yourself

external outline of the glass - **TEMPLE**
please do not change the color
and thickness of the line

all fonts converted to curve

smallest font used 8 pt

minimum thickness of lines used
in the design 0.2 mm

laser engraving area

we only use vector objects
(inscriptions, logos, characters)

the pattern for engraving will be prepared
in grey using 70 % black in C M Y K

when filling with pattern, please specify colour
(print palette in separate file)

ENGRAVING

Because of manual processing of the glass trophies,
template may slightly
differ from the final product.

KR2020

KR1818

KR1616

KR1414

KR1212

KR1010

engraving area